

KINGSWAY



INFRARED SENSORED AUTOMATIC SANITARY & PLUMBING PRODUCTS

Best choice to satisfy your automatic sanitary & plumbing needs



Widest product selection to provide one stop shopping.

Designed and manufactured in Taiwan with excellent experience and superb quality.

Easy installation , maintenance free and worry free

ELECTRONIC FAUCET



KF-510

FEATURES

- Water temperature is adjustable above deck.
- Spout made with polished chrome brass for durability.
- All electronic and solenoid parts are sealed and protected to resist water and moisture.
- Safeguard of self-locking after 1 minute of water flowing.

SPECIFICATIONS

Power	"AA" size Alkaline battery 4 PCs or DC 6V plug-in power adaptor
Battery life	500,000 uses
Sensing range	Adjustable

FEATURES

- Hot and cold water pre-tempered (KF-718A(CH) & KF-818A(CH)).
- Spout made with polished chrome brass for durability.
- All electronic and solenoid parts are sealed and protected to resist water and moisture.
- Safeguard of self-locking after 1 minute of water flowing.

SPECIFICATIONS

Power	CR-P2 DC6V Lithium battery or DC 6V plug-in power adaptor
Battery life	3 Years (at 50,000 uses per year)
Sensing range	Adjustable



KF-718A / KF-718A(CH)

KF-818A / KF-818A(CH)



KF-818R / KF-818R(CH)

FEATURES

- With override lever to enable the faucet into manual mode.
- The other features and specifications are the same as KF-818A series.
- Ideal to be used at hospitals and clinics.

FEATURES

- Wave hand within sensor range to turn on water and wave again to turn water off.
- All the electronic components and valve are located above deck.
- Selectable self-locking time for 6, 8 seconds, 3, 30 minutes.
- Ideal for hospitals, clinics, catering facilities, bar counters and kitchens.

SPECIFICATIONS

Power	CR-P2 DC6V Lithium battery 1 PC (included)
Battery life	3 Years (at 50,000 uses per year)
Sensing range	Non-Adjustable



KF-615-1

WALL-MOUNTED ELECTRONIC FAUCET



KF-618

FEATURES

- Place hand within sensing range to turn on water and leave sensing range to turn water off.
- Safeguard of self-locking after 1 minute of water flowing.
- Ideal for factories, laboratories and kitchens.

FEATURES

- Wave hand within sensing range to turn on water and wave again to turn water off.
- Safeguard of self-locking after 3 minutes of water flowing.
- Ideal for hospitals, medical clinics, laboratories and restaurant kitchens.

SPECIFICATIONS

Power	CR-P2 DC6V Lithium battery 1 PC (included)
Battery life	3 Years (at 50,000 uses per year)
Sensing range	Non-Adjustable



KF-615B



KF-615A



KF-616

ELECTRONIC SHOWER



KB-620

FEATURES

- Wave hand within sensing range to turn on water and wave again to turn water off.
- Selectable self-locking time of 3, 6, 9, 12 minutes.
- Powered by 1 PC of CR-P2 lithium battery with battery life 3 years.

ELECTRONIC FLUSH VALVE

FEATURES

- Direction of water inlet can be either from left or right side.
- Easy to install to convert the manual flush valve into automatic mode in minutes.
- With a mechanical override button to enable the valve into manual mode.
- With vacuum breaker flush tube.

SPECIFICATIONS

Power	CR-P2 DC6V Lithium battery 1 PC (included)
Battery life	3 Years (at 50,000 uses per year)
Operation water pressure	0.5 ~ 8 bar (7~114 psi)
Sensing range	Adjustable
Water inlet	3/4" or 1"
Water outlet	3/4", 1-1/4" or 1-1/2"
Flushing time	5~13 seconds adjustable



ELECTRONIC URINAL FLUSH VALVE



FEATURES

- With a mechanical override button to enable the valve into manual mode (KU-519 only).
- 2-Step automatic flush to keep urinal bowl clean.

SPECIFICATIONS

Power	CR-P2 DC6V Lithium battery 1 PC (included)
Battery life	3 Years (at 50,000 uses per year)
Sensing range	Adjustable

FEATURES

- Face plate, frame and control box are all made of stainless steel for durability.
- 2-Step automatic flush to keep urinal bowl clean.
- Special provided tool to remove faceplate for vandal proof.

SPECIFICATIONS

Power	CR-P2 DC6V Lithium battery 1 PC (included)
Battery life	3 Years (at 50,000 uses per year)
Sensing range	Adjustable
Dimension	KU-819-1: 200x100x75mm (7.9" x 3.9" x 3") KU-819-2: 100x100x75mm (3.9" x 3.9" x 3")



AUTOMATIC NON-AEROSOL DISPENSER

FEATURES

- Lasting longer than aerosol dispenser and with stronger deodorizing and air freshening capabilities.
- Water base, safe for environment.
- External cover is made of P.P. (Polypropylene) for anti-corrosion.
- Easy programming with 7.5, 15 and 30 minutes spray interval (AL-305).
- LCD display with programming functions such as on/off setting, clock setting, start/stop setting, spray interval setting and spray number counter (AL-306).

SPECIFICATIONS

Power	"AA" battery x 4 PCs
Dimension	H210xW80xD65mm (H8.2"xW3.2"xD2.6")
Fragrance refills	RL-355 (3,000 sprays)



AL-305

AL-306

RL-355

AUTOMATIC AEROSOL DISPENSER



AD-106

AD-108

AD-109

AD-110

AD-107

KA-230AD

GR-152

SPECIFICATIONS

Model	AD-106	AD-108	AD-109	AD-110	AD-107	KA-230AD
External cover material	P.P. (Polypropylene)					compact ABS
Power	"AA" battery x 2 PCs					"D" battery x 2 PCs
Dimension	H225 x W80 x D88mm (H8.9"xW3.2"xD3.5")					H235xW80xD90mm(H9.3"xW3.2"xD3.5")
Fragrance aerosol refills	GR-152 (3,000 sprays)					
Function	Easy programming with 7.5, 15 and 30 minutes spray interval.	With same function as AD-107 and KA-230AD, but is programmable for days and times of operation.				Intelligent design with full features of LCD display, on/off setting, clock setting, start/stop setting, spray interval setting an spray number counter.

WASHROOM ACCESSORIES



Sanitizer dispenser (for urinal & toilet)

Capacity: 300 ml (3,000 flushing times)
Refill: UR-957



US-906 / US-907 / US-910

Foam soap dispenser

Capacity: 600 ml (800 uses)
Refill: SR-452 concentrated liquid soap



SD-402



DC-405



HS-453



SS-455

Toilet seat cleaner

Capacity: 320 ml (2,500 sprays)
Refill: - HS-452 Antibacterial Soap
- SS-455 Toilet Seat Sanitizer

Stainless steel soap dispenser

Capacity: 1200 ml



A600



A605



A845

Stainless Steel Jumbo Roll Toilet Tissue Dispenser

Capacity: 250M long up to 4-14" 2-ply tissue

AUTOMATIC FOAM DISPENSER

FEATURES

- Quick, uniform and complete coverage of user's hands.
- Modular design to ensure easy maintenance.
- Cost saving, approximately 1/3 soap delivered than liquid soap dispenser.

SPECIFICATIONS

Power	"AA" size Alkaline battery 4 PCs
Capacity	800ml, refillable reservoir
Pump	0.75ml (10cm ³) for foam type



KS-800F

AUTOMATIC SOAP DISPENSER



HK-RSD01



HK-RSD02



HK-RSD03



HK-RSD04



HK-RSD05



HK-RSD06



HK-RSD07

FEATURES

- Housing is made of stainless steel for models 01 & 07 or aluminum steel for models 02 to 06.
- Modular design to ensure easy maintenance.
- Can be used for liquid soap, liquid alcohol, alcohol gel, sterilized iodine and disinfectant

SPECIFICATIONS

Power	"AA" size Alkaline battery 6 PCs
Capacity	900 ml
Battery life	50,000 uses

FEATURES

- Housing material: KS-950DA - ABS; KS-950SAR - stainless steel.
- Modular design to ensure easy maintenance.
- Can be used for liquid soap, liquid alcohol, alcohol gel, sterilized iodine and disinfectant

SPECIFICATIONS

Power	"C" size Alkaline battery 3 PCs
Capacity	950 ml
Battery life	50,000 uses



KS-950SAR



KS-950DA



ASD-750



ASD-950

FEATURES

- Number of drops can be adjusted from 1 drop to 9 drops.
- No dripping after dispensing.
- Models ASD-750A & ASD-950A can be used for alcohol, iodine and disinfectant.
- Ideal for hospital operating rooms, nursing stations and medical clinics.

SPECIFICATIONS

Model No	ASD-750 & ASD-750A	ASD-950 & ASD-950A
Power	"C" size Alkaline battery x 4 pcs	
Capacity	750 ml	950 ml
Battery life	50,000 uses	



ASD-750A



ASD-950A

AUTOMATIC HAND DRYER WITH DIGITAL VIDEO DISPLAY

FEATURES

- Automatic hand dryer with 7" TFT-LCD panel.
- Video, slide and music playback functions are available.
- Support several types of memory card and file format.
- Operating Voltage: 230-240 VAC, 50/60Hz, 2000-2200 watts (110-120VAC, 1800-2200 watts).
- Cover material: stainless steel 1.5mm thick.
- Dimension: W278 x H418 x D134mm(11"x16.5"x5.25").



HK-2200SA(DP)

HIGH SPEED HAND DRYER



HK-JA01



HK-JA02



HK-JA03



HK-JA04



HK-JA05

FEATURES

- High speed, less than 10-15 seconds dry time.
- Low power consumption at 1,600 watts.
- High brightness LED to increase the ease and delight of use.
- 3-step safeguard protection to prevent overheating.

SPECIFICATIONS

Model	HK-JA01	HK-JA02	HK-JA03	HK-JA04	HK-JA05
External cover	Steel cover Porcelain enameled coating (t:1.6mm)	Steel cover Bright chromed (t:1.6mm)	Steel cover Satin chromed (t:1.6mm)	Stainless steel Bright finished (t:1.5mm)	Stainless steel Satin finished (t:1.5mm)
Electrical spec.	110-120 VAC or 220-240 VAC; 50/60Hz				
Warm air speed output	75-100 m/s (169-225 mi/hr), adjustable				
Motor	Brush type; dual ball bearings 350-700 watts, 12,000-18,000 R.P.M. adjustable				
Heater	450-900 watts, adjustable				
Dimension	W205 x H287 x D180mm (8.1" x 11.3"x7.1")				

RECESSED AUTOMATIC HAND DRYER

FEATURES

- Approximately 20-25 seconds drying time.
- 2 vandal-proof lock screws and key wrench.
- 3-step safeguard protection to prevent overheating.

SPECIFICATIONS

External cover	Stainless steel
Electrical spec.	110-120 Vac or 220-240 Vac; 50/60Hz; 2200 watts
Effective airflow	362 m ³ /h (212 C.F.M.)
Motor	Brush type; 200 watts, 3,800 R.P.M.
Heater	2000 watts
Dimension	W341xH361xD156mm(13.4"x14.2"x6.1")



HK-2200SA(R)

HAND DRYER



KH-180A



KH-180P



KH-180SA



KH-180SP

FEATURES

- Electronic control assembly is fully moisture proof.
- Safeguard protection of automatically cutting off after a continuous use for 2 minutes.
- 3-step safeguard protection to prevent overheating.

SPECIFICATIONS

Model	KH-180A / KH-180P	KH-180SA / KH-180SP	KH-180CA / KH-180CP
External cover	Aluminum Alloy	Stainless steel #304; t:1.2mm	Satin chrome-plated
Electrical spec.	110-120 VAC or 220-240 VAC; 50/60Hz		
Motor	Brushless induction motor, 100W 3450 r.p.m. (60Hz), 2850 r.p.m.(50Hz)		
Total wattage	1800 watts (2200 watts is also available)		
Dimension	W248 x H220 x D170mm (9.8"x8.7"x6.7")		



KH-180CA



KH-180CP



HK-1800PA



HK-1800PS

FEATURES

- Electronic control assembly is fully moisture proof.
- Safeguard protection of automatically cutting off after a continuous use for 2 minutes.
- 3-step safeguard protection to prevent overheating.

SPECIFICATIONS

Model	HK-1800PA	HK-1800PS
Operation	Infrared sensor, Automatic	Push button
External cover	High grade fire retardant ABS, 3.0mm thick	
Voltage / Frequency	110-120 Vac or 220-240 Vac; 50/60Hz	
Motor	Brushless induction motor, 80W 3400 r.p.m. (60Hz), 2850 r.p.m.(50Hz)	
Total wattage	1800 watts	
Dimension	W268 x H220 x D170mm (10.6"x8.7"x6.7")	

Kingsway Technology Inc.

11th Fl., No. 27, Sec. 3, Chung Shan N. Rd., Taipei, Taiwan, R.O.C.

Tel:886-2-25916311 <http://www.kingswaytech.com>

Fax:886-2-25916321 E-mail:info@kingswaytech.com

